

# -40 ~ 120℃ 히터/쿨러 제어 고정밀 온도조절모듈 (P2679-1)



## **Specifications:**

#### Features:

A mini digital temperature controller.

With large and clear LCD display for better readability.

Wide temperature measuring range.

Heating and cooling control.

Temperature calibration function.

Delay protection function.

All parameters can be set to default setting after short circuit.

Alarm function, can set both a high and a low temperature limit, when the temperature is beyond the compass of limits, there will be alarm sound and the indicator flashes.

Used for domestic freezer, water tanks, refrigerator, industrial chiller, boiler, steamer, industrial equipments and other temperature-controlled systems.

#### **Specifications:**

Working voltage: 220V  $\pm$ 10% Relay rated current: 10A Power consumption:  $\leq$ 3W Measurement range: -40 °C ~ 120 °C Measurement precision: 0.1 °C Measurement error:  $\pm$ 0.5 °C Control range: -40 °C ~120 °C Control precision: 0.1 °C Working temperature: -20 °C ~70 °C Temperature sensor: NTC 25 °C = 10K B3435 Dimension of whole unit:75x34.5x85mm (WHD) Panel cutting dimension:71 (W)x29(H) Package weight: 195g

### Package Includes: H9439

- 1 \* Temperature Controller
- 1 \* Temperature Sensor
- 1 \* Instruction Manual



509 Technozone EZEN, 2979 Hagun-ri, Yangchon-myeon, Gimpo-si, Gyeonggi-do, KOREA TEL : +82-2-70-8224-4400 FAX : +82-2-505-498-4400

